



Verdelli International Srl

EQUIPMENT AND SPARE PARTS
LIFTING, PILING, EARTHMOVING MACHINERY
DEMOLITION TOOLS

ELECTROHYDRAULIC CLAMSHELL 2 ORIZONTAL CYLINDERS

MODEL	CAPAC.	ENGINE	PRESSURE	TIME		CLAM POWER	WEIGHT kg	DIMENSIONS (mm)				
	m ³	KW	kg/cm ²	Op.	Cl.	kg		A	B	C	D	E
M.E.-O. 2/750	0,75	11	130	5	7	6500	1500	1500	2100	1000	1300	1300
M.E.-O. 2/1000	1	15	130	5	7	7000	1500	1605	2350	1360	1460	1320
M.E.-O. 2/1500	1,5	15	130	5	8	7000	2200	1850	2750	1400	1700	1580
M.E.-O. 2/2000	2	18,5	130	5	8	7000	2700	2100	3120	1470	1950	1740
M.E.-O. 2/2500	2,5	18,5	130	5	8	8000	2900	2100	3250	1470	2000	1740
M.E.-O. 2/3000	3	18,5	130	5	8	9000	3200	2100	3600	1670	2000	1800
M.E.-O. 2/4000	4	22	130	6	10	9500	4000	2300	3400	1800	2350	2050
M.E.-O. 2/5000	5	30	130	10	14	13000	5000	2500	4000	2000	2650	2350
M.E.-O. 2/6000	6	30	140	10	14	15000	5500	2650	4200	2100	2800	2500
M.E.-O. 2/7000	7	30	140	10	14	15000	6000	2850	4400	2200	3000	2600
M.E.-O. 2/8000	8	37,5	140	12	18	15500	7000	3000	4600	2300	3200	2800
M.E.-O. 2/10000	10	42	140	12	18	18000	8000	3300	4800	2500	3400	3000
M.E.-O. 2/12000	12	42	140	16	24	20000	9000	3600	5000	2700	3600	3200

